



JP10075287



INVESTOR IN PEOPLE

- PN - JP10075287 A 19980317
PD - 1998-03-17
PR - JP19960230377 19960830
OPD - 1996-08-30
TI - PORTABLE VIDEO TELEPHONE
AB - PROBLEM TO BE SOLVED: To change the direction of a camera without moving a body at the use of the camera by protecting a lens and a camera part unless the camera is used, permitting an image not to be fetched and eliminating the psychological uneasiness of a user that the image is being transmitted. SOLUTION: The camera 101 is provided so as to freely make an appearance against a display part 111. A lock release button 103 is depressed when the camera is used so as to expose the camera 101 to the outside of the display part 111. The exposed camera 101 can be rotated so as to change an angle without moving an operating part 109 and the display part 111. Unless the camera is used, it is pushed-down and contained inside the display part 111.
- IN - HATA YOSHIYUKI; URABE KENZO; TSUNODA HISAMI; ONO YASUHIRO; SUZUKI HIROSHI
PA - KOKUSAI ELECTRIC CO LTD
IC - H04M1/02; H04M1/00; H04M1/21; H04M11/06; H04N5/225; H04N7/14
FI - H04M1/00&U; H04M1/02&C; H04M1/21&Z; H04M11/06; H04N5/225&F; H04N7/14
FT - 5C022/AA12; 5C022/AC03; 5C022/AC27; 5C022/AC32; 5C022/AC42; 5C022/AC54;
5C022/AC62; 5C022/AC63; 5C022/AC66; 5C022/AC71; 5C022/AC72; 5C022/AC73;
5C022/AC75; 5C022/AC77; 5C064/AB01; 5C064/AB06; 5C064/AC04; 5C064/AC06;
5C064/AC12; 5C064/AC16; 5C064/AC17; 5C064/AD01; 5C064/AD06; 5C064/AD14;
5K023/AA07; 5K023/BB11; 5K023/BB26; 5K023/DD08; 5K023/MM20; 5K023/MM25; 5K023/PP02
; 5K027/AA11; 5K027/BB02; 5K027/HH29; 5K101/KK04; 5K101/LL12; 5K101/NN06; 5K101/NN18
© WPI / DERWENT
- TI - Portable video telephone with camera - has display part whose detachable camera is exposed only under use state, by pushing lock release button
PR - JP19960230377 19960830
PN - JP10075287 A 19980317 DW199821 H04M1/02 012pp
PA - (KOKZ) KOKUSAI DENKI KK
IC - H04M1/00 ;H04M1/02 ;H04M1/21 ;H04M11/06 ;H04N5/225 ;H04N7/14
AB - J10075287 The telephone has a display part (111) with a detachable camera (101). The camera is exposed to the externals, when a lock release button (103) is pushed.
- The camera is pushed inside the display part, when not in use. The display part is rotatably attached to an operating part (109) by a hinge part (112).
- ADVANTAGE - Prevents incorrect video transmission thereby securing privacy. Obtains compactness and enables folding of video telephone. Improves safety and reliability of camera.
- (Dwg. 1/13)
OPD - 1996-08-30
AN - 1998-236944 [21]
© PAJ / JPO
- PN - JP10075287 A 19980317
PD - 1998-03-17
AP - JP19960230377 19960830
IN - HATA YOSHIYUKI;URABE KENZO;TSUNODA HISAMI;ONO YASUHIRO;SUZUKI HIROSHI
PA - KOKUSAI ELECTRIC CO LTD
TI - PORTABLE VIDEO TELEPHONE



JP#0076287

INVESTOR IN PEOPLE

AB

PROBLEM TO BE SOLVED: To change the direction of a camera without moving a body at the use of the camera by protecting a lens and a camera part unless the camera is used, permitting an image not to be fetched and eliminating the psychological uneasiness of a user that the image is being transmitted.

- **SOLUTION:** The camera 101 is provided so as to freely make an appearance against a display part 111. A lock release button 103 is depressed when the camera is used so as to expose the camera 101 to the outside of the display part 111. The exposed camera 101 can be rotated so as to change an angle without moving an operating part 109 and the display part 111. Unless the camera is used, it is pushed-down and contained inside the display part 111.

- I - H04M1/02 ;H04M1/00 ;H04M1/21 ;H04M11/06 ;H04N5/225 ;H04N7/14